

# AquaCooler

The Aqua Cooler Drinking water fountain has durable push button operated bubbler and Glass Filler. It is mains connected and can be fitted with a Carbon Filter to remove the taste and smell of Chlorine. The waste water is removed via a 32mm diameter Flexible and extendable waste pipe which connects to a standard dishwasher/washing machine waste trap

## Water Flow control

The Water Fountain is rated to supply 1.7 litres per minute. An automatic self regulating control is fitted to overcome varying mains pressure.

## Cabinet

Polished stainless steel top. Dark Grey colour bond(BHP) metal side panels. Easily removable front panel for ease of filter exchange & servicing.

## Refrigeration System

Non Toxic, non flammable and environmentally sympathetic R-134a refrigerant. The refrigerant flow is controlled by a capillary tube with no moving parts. To provide for maximum heat exchange (and increase cold water capacity) a suction line is fitted to remove the heated air.

## Cooling System

Stainless Steele 1.5 Litre cold water tank with chilling chamber to meet peak demand.

Cooling Capacity 19 l per hour to 10 C

from water inlet temperature of 26.7 C

and ambient temperature of 32.2 C

The hourly Cooling Capacity increases exponentially if the Incoming water temperature is less than 26.7 C, as will be the case in the UK.

## Compressor & Condenser

Compressor: 1/5 h.p. capacity 230 watt

Condenser: Fan assisted high performance compact condenser made of copper and aluminium construction.

## Power supply

240 Volt, 50Hz. 3 pin plug and 200 cm power cord.

## Dimensions & Weight

Dimensions: H 110 cm; W 35cm; D 35cm

Weight: 32 Kg



 **LINK VENDING**  
the charity-linked vending company.

The Charity – Linked Vending Company

Tel 020 8669 2002

Fax 020 8669 9666

email [sales@linkvending.co.uk](mailto:sales@linkvending.co.uk)

[www.linkvending.co.uk](http://www.linkvending.co.uk)