

# G-SNACK

**COMBINED**

Variable Temperature

Perishable Product Area

**2°C**

← →

**2°C Cool**

Maximum flexibility

Food area height is adjustable

**ALL FOOD**

One Temperature

**SPEEDY ELEVATOR**

Delicate and/or fragile products can be sold also eye-height position! Speedy delivery of the products is guaranteed!

**BANKABLE**

**PATENTED** **COUPLING SYSTEM** for easy spiral orientation

The spiral can be easily positioned in 8 angles, without taking out or pull it. Simply turn the spiral to set the ideal position. We are the first and only one to introduce this innovation in the market!

**Easy and quick; clip-in, clip-out!**

# G-SNACK

## Advanced Software Programming

Our Advanced SOFTWARE allow the machine programmed in Energy Saving modes.

### LIGHT CONTROL

TURNED OFF - when the machine is NOT in function, according to the set value of the program. (Set-up can be done by the days of the week, start and stop time, also with "during not-vending period").

### SAFETY HEALTH CONTROL

When the temperature stays over the set temperature for more than 30 min. sales will be blocked. (Programmable on the selected shelves, which cover all the lower shelves).



**ECO Project**

**LOW ENERGY CONSUMPTION**

**8.50** kWh/24h

Room Temperature **32°C** (65% R.H.)  
2° C combined cooling solution.

*Guaranteed Temperature Function*  
to offer product safety for the consumers

### SECURITY



Option



Option



ANTI-VANDALISM KEY BOARD

	G-Snack Master 6°C	G-Snack FOOD Master 2°C	G-Snack Slave 6°C	G-Snack FOOD Slave 2°C
No. of selections	56	56	56	56
No. of shelves	7	7	7	7
H x W x D (mm)	1830 x 955 x 850	1830 x 955 x 850	1830 x 805 x 850	1830 x 805 x 850
Weight (in KG)	310 kg	310 kg	245 kg	245 kg
Control	Executive: MDB	Executive: MDB	Executive: MDB	Executive: MDB
Temperature control	by thermostat	Electronic with digital display	by thermostat	Electronic with digital display
Temperature range	6-25°C	2°C-25°C	6-25°C	2°C-25°C
Power consumption	400W	550W	350W	500W
Power Supply	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz

#### Standard cabinet colours



#### Standard ABS panel colour



#### Option:

Customized cabinet/ABS colour on request

Branding on ABS in silk screen print

Double spiral motor

Various product fitting kits



the charity-linked vending company.

The Charity – Linked Vending Company

Tel 020 8669 2002

Fax 020 8669 9666

email sales@linkvending.co.uk

www.linkvending.co.uk