


- Easy programming using selection button sequence
- Electronic control and data-recording
- Energy Management by real time clock
- Electronically controlled forced air-cooling
- Each column has individual vend motor
- 24 V D/C motors
- Interchangeable parts



Narrowstack



Technical Features	VDI 408-8	VDI 476-7	VDI 510-10	VDI 544-8	VDI 680-10
Selections / Columns	10 / 8	10 / 7	10 / 10	10 / 8	10 / 10
Max. product length (mm)	368	505	368	505	505
Max. product Ø (mm)	72	72	72	72	72
<b>Capacities:</b>					
Can 0,33 l	408	476	510	544	680
PET bottle 0,50 l	136	238	170	272	340
<b>Dimensions and weights:</b>					
H x W x D (mm)	1830 x 850 x 790	1830 x 750 x 940	1830 x 1010 x 790	1830 x 850 x 940	1830 x 1010 x 940
Weight	295 kg	310 kg	330 kg	335 kg	388 kg
Refrigeration	899 W / 12cc	997 W / 14cc	899 W / 12cc	997 W / 14cc	997 W / 14cc
Power supply	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz
Max. power consumption	820 W	875 W	820 W	875 W	875 W
Control			Executive / MDB		
Cabinet			Zinc powder coated steel		
Standard colour black	yes	yes	yes	yes	yes
<b>Options:</b>					
Cabinet Colour on request	yes	yes	yes	yes	yes
Two-line LCD display	yes	yes	yes	yes	yes
Stack assembly for product Ø 74 mm	-	-	-	yes	yes
Security cash systems	yes	yes	yes	yes	yes
Safety sliding coin insert	yes	yes	yes	yes	yes
Anti-rain kit IP 34	yes	yes	yes	yes	yes
Loading rack	yes	yes	yes	yes	yes

Specifications subject to change | July 2008



the charity-linked vending company.

The Charity – Linked Vending Company

Tel 020 8669 2002

Fax 020 8669 9666

email sales@linkvending.co.uk

www.linkvending.co.uk