

- Each column has individual vend motor
- Thermostatically controlled forced air-cooling
- Product pre-cooling
- Foamed cabinet
- Anti-theft device
- Interchangeable parts



Superstack

Technical Features	VDI 100-5	VDI 189-5	VDI 217-6	VDI 218-5	VDI 254-7
Selections / Columns	5 / 5	5 / 5	6 / 6	6 / 5	7 / 7
Max. product length (mm)	300	300	300	300	300
Max. product Ø (mm)	66	66	66	74	68,5
Capacities:					
Can 0,33 l	190	300	360	300	434
PET bottle 0,50 l	95	150	180	150	224
Glass RET-bottle 0,20 l	100	175	210	175	245
Glass RET-bottle 0,33 l	95	150	180	150	231
Glass NRET-bottle 0,33 l	95	150	180	150	231
Glass RET-bottle 0,50 l	-	-	-	145	210
Dimensions and weights:					
H x W x D (mm)	1422 x 705 x 745	1830 x 705 x 745	1830 x 855 x 745	1830 x 855 x 745	1830 x 1010 x 745
Weight	186 kg	235 kg	264 kg	255 kg	295 kg
Refrigeration	0,340 kW	0,340 kW	0,519 kW	0,519 kW	0,519 kW
Power supply	230V / 50 Hz	230V / 50 Hz	230V / 50 Hz	230V / 50 Hz	230V / 50 Hz
Max. power consumption	630 W	670 W	780 W	780 W	780 W
Control	BDV / Executive / MDB				
Cabinet	Zinc powder coated steel				
Standard colour black	yes	yes	yes	yes	yes
Options:					
Cabinet Colour on request	yes	yes	yes	yes	yes
Two-line LCD display	yes	yes	yes	yes	yes

Specifications subject to change | July 2006



the charity-linked vending company.

The Charity – Linked Vending Company
 Tel 020 8669 2002
 Fax 020 8669 9666
 email sales@linkvending.co.uk
 www.linkvending.co.uk